

**Paper 3C/4C: Further Mechanics 1 Mark Scheme**

| Question  | Scheme   | Marks | AOs  |
|---|--|-------|------|
| 1   | Use Impulse-momentum principle   | M1    | 2.1  |
|   | $2\mathbf{i} - \mathbf{j} = 0.5\mathbf{v} - 0.5(4\mathbf{i} + \mathbf{j})$   | A1    | 1.1b |
|   | $\frac{1}{2}\mathbf{v} = 4\mathbf{i} - \frac{1}{2}\mathbf{j}, \quad \mathbf{v} = 8\mathbf{i} - \mathbf{j} \text{ (m s}^{-1}\text{)}$ | A1    | 1.1b |
|   | Use of $\text{KE} = \frac{1}{2}m \mathbf{v} ^2 - \frac{1}{2}m \mathbf{u} ^2$   | M1    | 2.1  |
|   | $= \frac{1}{2} \times 0.5 \times \{(64 + 1) - (16 + 1)\}$  | A1    | 1.1b |
|   | $= \frac{1}{4} \times 48 = 12 \text{ (J)} \quad *$   | A1*   | 1.1b |
|   |  | (6)   |      |
| <b>(6 marks)</b>  |  |       |      |
| <b>Notes:</b>   |  |       |      |
| <p><b>M1:</b> Difference of terms &amp; dimensionally correct</p> <p><b>A1:</b> Correct unsimplified equation</p> <p><b>A1:</b> cao</p> <p><b>M1:</b> Must be a difference of two terms<br/>Must be dimensionally correct</p> <p><b>A1:</b> Correct unsimplified equation</p> <p><b>A1*:</b> Complete justification of given answer</p> |  |       |      |

| Question   | Scheme  | Marks      | AOs  |
|--|---|------------|------|
| <b>2(a)</b>  | $R = 5g \cos \alpha \left( = 5g \times \frac{4\sqrt{3}}{7} = 48.497\dots \right)$ | M1         | 3.4  |
|  | Force due to friction = $\mu \times 5g \cos \alpha$                               | M1         | 3.4  |
|  | Work-Energy equation  | M1         | 3.4  |
|  | $\frac{1}{2} \times 5 \times 64 = 5 \times 9.8 \times 14 \sin \alpha + 14\mu R$   | A1         | 1.1b |
|  | $\mu = 0.0913$ or $0.091$   | A1         | 1.1b |
|  |   | <b>(5)</b> |      |
| <b>(b)</b>   | Appropriate refinement  | B1         | 3.5c |
|  |   | <b>(1)</b> |      |
| <b>(6 marks)</b>   |   |            |      |
| <b>Notes:</b>  |   |            |      |
| <p><b>(a)</b></p> <p><b>M1:</b> Condone sin/cos confusion</p> <p><b>M1:</b> Use of <math>\mu \times</math> their R</p> <p><b>M1:</b> Must be using work-energy. Requires all terms<br/>Condone sin/cos confusion, sign errors and their R</p> <p><b>A1:</b> Correct in <math>\theta</math> and <math>\mu R</math></p> <p><b>A1:</b> Accept 0.0913 or 0.091</p> |   |            |      |
| <p><b>(b)</b></p> <p><b>B1:</b> e.g.</p> <ul style="list-style-type: none"> <li>- do not model the parcel as a particle and therefore take air resistance into account</li> <li>- take into account the dimensions/uniformity of the parcel</li> </ul>   |   |            |      |

| Question  | Scheme  | Marks      | AOs  |
|---|---|------------|------|
| <b>3(a)</b>   | Use NEL to find the speed of particle after the first impact<br>$= eu = \frac{3}{4}u \frac{\pi}{2}$                               | B1         | 3.4  |
|   | Impulse = $\lambda mu = mv - mu = \pm \left[ \frac{3}{4}mu - (-mu) \right]$   | M1         | 3.1b |
|   | $\lambda = \frac{7}{4}$   | A1         | 1.1b |
|   |   | <b>(3)</b> |      |
| <b>(b)</b>  | Use NEL to find the speed of the particle after the second impact<br>$= \frac{3}{4} \times \frac{3}{4}u = \frac{9}{16}u$          | B1         | 3.4  |
|   | Use of $s = vt$ to find total time  | M1         | 3.1b |
|   | $7 = \frac{2}{u} + \frac{4}{\frac{3}{4}u} + \frac{2}{\frac{9}{16}u} \left( = \frac{2}{u} + \frac{16}{3u} + \frac{32}{9u} \right)$ | A1         | 1.1b |
|   | Solve for $u$ : $63u = 18 + 48 + 32$  | M1         | 1.1b |
|   | $u = \frac{98}{63} = \frac{14}{9} (= 1.5\dot{6})$   | A1         | 1.1b |
|   |   | <b>(5)</b> |      |
| <b>(8 marks)</b>  |   |            |      |
| <b>Notes:</b>   |   |            |      |
| <b>(a)</b>  |   |            |      |
| <b>B1:</b> Using Newton's experimental law as a model to find the speed after the first impact    |   |            |      |
| <b>M1:</b> Must be a difference of two terms, taking account of the change in direction of motion |   |            |      |
| <b>A1:</b> cao  |   |            |      |
| <b>(b)</b>  |   |            |      |
| <b>B1:</b> Using NEL as a model to find the speed after the second impact                         |   |            |      |
| <b>M1:</b> Needs to be used for at least one stage of the journey                                 |   |            |      |
| <b>A1:</b> Ur equivalent  |   |            |      |
| <b>M1:</b> Solve their linear equation for $u$  |   |            |      |
| <b>A1:</b> Accept 1.56 or better  |   |            |      |

| Question   | Scheme   | Marks      | AOs  |
|--|--|------------|------|
| <b>4(a)</b>  | Complete strategy to find the kinetic energy after the second impact   | M1         | 3.1b |
|  | Parallel to $AB$ after collision: $u \cos 60^\circ$  | M1         | 3.1b |
|  | Perpendicular to $AB$ after collision: $\frac{1}{\sqrt{3}}u \sin 60^\circ$   | M1         | 3.4  |
|  | Components of velocity after first impact: $\frac{u}{2}, \frac{u}{2}$  | A1         | 1.1b |
|  | Parallel to $BC$ after collision: $\frac{u}{2} \left( u \times \frac{1}{\sqrt{3}} \sin 60^\circ \right)$   | M1         | 3.1b |
|  | Perpendicular to $BC$ after collision: $\sqrt{\frac{2}{5}} \times \frac{u}{2} \left( = \frac{1}{\sqrt{10}}u \right)$<br>$\left( \sqrt{\frac{2}{5}} \times u \cos 60^\circ \right)$ | M1         | 3.4  |
|  | Components of velocity after second impact: $\frac{u}{2}, \frac{u}{\sqrt{10}}$   | A1         | 1.1b |
|  | Final KE = $\frac{1}{2}m \left( \frac{u^2}{4} + \frac{u^2}{10} \right) \left( = \frac{mu^2}{2} \times \frac{7}{20} \right)$  |            |      |
|  | Fraction of initial KE = $\frac{\frac{mu^2}{2} \times \frac{7}{20}}{\frac{mu^2}{2}} = \frac{7}{20} = 35\% *$   | A1*        | 2.2a |
|  | <b>(8)</b>   |            |      |
| <b>(b)</b>   | The answer is too large - rough surface means resistance so final speed will be lower  | B1         | 3.5a |
|  |  | <b>(1)</b> |      |
| <b>(9 marks)</b>   |  |            |      |
| <b>Notes:</b>  |  |            |      |
| <b>(a)</b>   |  |            |      |
| <b>M1:</b> Use of CLM parallel to the wall. Condone sin/cos confusion                                |  |            |      |
| <b>M1:</b> Use NEL as a model to find the speed perpendicular to the wall. Condone sin/cos confusion |  |            |      |
| <b>A1:</b> Both components correct with trig substituted (seen or implied)                           |  |            |      |
| <b>M1:</b> Use of CLM parallel to the wall. Condone sin/cos confusion                                |  |            |      |
| <b>M1:</b> Use NEL as a model to find the speed perpendicular to the wall. Condone sin/cos confusion |  |            |      |
| <b>A1:</b> Both components correct with trig substituted (seen or implied)                           |  |            |      |
| <b>M1:</b> Correct expression for total KE using their components after 2nd collision                |  |            |      |
| <b>A1*:</b> Obtain <b>given answer</b> with sufficient working to justify it                         |  |            |      |
| <b>(b)</b>   |  |            |      |
| <b>B1:</b> Clear explanation of how the modelling assumption has affected the outcome                |  |            |      |

| Question   | Scheme   | Marks      | AOs  |
|--|--|------------|------|
| <b>5(a)</b>  | Use of $P = Fv$ : $F = \frac{12000}{20}$                                     | B1         | 3.3  |
|  | Equation of motion: $F - (200 + 2v) = 600a$                                  | M1         | 3.4  |
|  | $600 - 240 = 600a$   | A1ft       | 1.1b |
|  | $360 = 600a, a = 0.6 \text{ (m s}^{-2}\text{)}$                              | A1         | 1.1b |
|  |  | <b>(4)</b> |      |
| <b>(b)</b>   | Equation of motion:  | M1         | 3.3  |
|  | $\frac{12000}{w} - (200 + 2w) - 600g \sin \theta = -600 \times 0.05$         | A1         | 1.1b |
|  |  | A1         | 1.1b |
|  | 3 term quadratic and solve: $2w^2 + 590w - 12000 = 0$                        | M1         | 1.1b |
|  | $w = \frac{-590 + \sqrt{590^2 + 96000}}{4} = 19.1 \text{ (m s}^{-1}\text{)}$ | A1         | 1.1b |
|  | <b>(5)</b>   |            |      |
| <b>(9 marks)</b>   |  |            |      |
| <b>Notes:</b>  |  |            |      |
| <b>(a)</b>   |  |            |      |
| <b>B1:</b> 600 or equivalent   |  |            |      |
| <b>M1:</b> Use the model to form the equation of motion<br>Must include all terms .Condone sign errors                 |  |            |      |
| <b>A1ft:</b> Correct for their $F$   |  |            |      |
| <b>A1:</b> cao   |  |            |      |
| <b>(b)</b>   |  |            |      |
| <b>M1:</b> Use the model to form the equation of motion<br>All terms needed. Condone sign errors and sin/cos confusion |  |            |      |
| <b>A1:</b> All correct A1A1<br>One error A1A0  |  |            |      |
| <b>M1:</b> Dependent on the preceding M1. Use the equation of motion to form a 3-term quadratic<br>in $w$ only         |  |            |      |
| <b>A1:</b> Accept 19. Do not accept more than 3 s.f.   |  |            |      |

| Question  | Scheme  | Marks | AOs  |
|---|---|-------|------|
| <b>6(a)</b>   |   |       |      |
|   | Overall strategy to find $\mathbf{V}_A$   | M1    | 3.1a |
|   | Velocity of A perpendicular to loc after collision = $3\mathbf{j}$ ( $\text{m s}^{-1}$ )                    | B1    | 3.4  |
|   | CLM parallel to loc   | M1    | 3.1a |
|   | $2m \times 3 - 3m \times 5 = 3mw - 2mv$ ( $-9 = 3w - 2v$ )  | A1    | 1.1b |
|   | Correct use of impact law   | M1    | 3.1a |
|   | $v + w = \frac{1}{4}(3 + 5)$ ( $= 2$ )  | A1    | 1.1b |
|   | Solve for $w$<br>$3w - 2v = -9$<br>$2v + 2w = 4$  |       |      |
|   | $\mathbf{v}_B = -\mathbf{i} + 2\mathbf{j}$ ( $\text{m s}^{-1}$ ),   | A1ft  | 1.1b |
|   |   | (7)   |      |
| <b>(b)</b>  | $\cos \theta = \frac{(-5\mathbf{i} + 2\mathbf{j}) \cdot (-\mathbf{i} + 2\mathbf{j})}{\sqrt{29}\sqrt{5}}$    | M1    | 3.1a |
|   | $\theta = 41.63\dots^\circ = 42^\circ$ (nearest degree)   | A1    | 1.1b |
|   | Alternative method: $\tan^{-1} 2 - \tan^{-1} \frac{2}{5} = 41.63\dots^\circ = 42^\circ$<br>(nearest degree) |       |      |
|   |   | (2)   |      |
| <b>(9 marks)</b>  |   |       |      |
| <b>Notes:</b>   |   |       |      |
| <b>(a)</b>  |   |       |      |
| <b>M1:</b> Correct overall strategy to form sufficient equations and solve for $\mathbf{V}_A$         |   |       |      |
| <b>B1:</b> Use the model to find the component of $\mathbf{V}_A$ perpendicular to the line of centres |   |       |      |
| <b>M1:</b> Use CLM to form equation in $v$ and $w$ . Need all 4 terms, dimensionally correct          |   |       |      |
| <b>A1:</b> Correct unsimplified   |   |       |      |
| <b>M1:</b> Must be used the right way round   |   |       |      |
| <b>A1:</b> Correct unsimplified   |   |       |      |
| <b>A1ft:</b> $\mathbf{v}_B$ correct. Follow their $2\mathbf{j}$                                       |   |       |      |
| <b>(b)</b>  |   |       |      |
| <b>M1:</b> Complete method for finding the required angle. Follow their $\mathbf{v}_B$                |   |       |      |
| <b>A1:</b> cao  |   |       |      |

| Question          | Scheme  | Marks      | AOs          |
|-------------------|---|------------|--------------|
| <b>7(a)</b>       | In equilibrium $\Rightarrow$ no resultant vertical force  | M1         | 2.1          |
|                   | $\frac{3mgx}{a} = mg$   | A1         | 1.1b         |
|                   | $x = \frac{a}{3}, \quad d = \frac{4}{3}a \quad *$   | A1*        | 2.2a         |
|                   |   | <b>(3)</b> |              |
| <b>(b)</b>        | Equation of motion:   | M1         | 3.1a         |
|                   | $\frac{3mga}{a} - mg = m\ddot{x}$   | A1         | 1.1b         |
|                   | $\ddot{x} = 2g$   | A1         | 1.1b         |
|                   |   | <b>(3)</b> |              |
| <b>(c)</b>        | Max speed at equilibrium position   | B1         | 3.1a         |
|                   | Work energy & use of EPE = $\frac{\lambda x^2}{2a}$   | M1         | 3.1a         |
|                   | $\frac{3mga^2}{2a} = \frac{3mg\left(\frac{a}{3}\right)^2}{2a} + \frac{1}{2}mv^2 + mg\frac{2a}{3}$                         | A1<br>A1   | 1.1b<br>1.1b |
|                   | $\frac{1}{2}v^2 = ga\left(\frac{3}{2} - \frac{1}{6} - \frac{2}{3}\right) = \frac{2}{3}ga, \quad v = \sqrt{\frac{4ga}{3}}$ | A1         | 1.1b         |
|                   |   | <b>(5)</b> |              |
| <b>(d)</b>        | At max ht. KE = 0. EPE lost = GPE gained  | M1         | 3.1a         |
|                   | $\frac{3mga^2}{2a} = mgh$   | A1         | 1.1b         |
|                   | $OB = \frac{a}{2}$  | A1         | 1.1b         |
|                   |   | <b>(3)</b> |              |
| <b>(14 marks)</b> |   |            |              |

**Question 7 notes:****(a)****M1:** Use  $T = \frac{\lambda x}{a}$  to form equation for equilibrium**A1:** Correct unsimplified equation**A1\*:** Requires sufficient working to justify given answer plus a 'statement' that the required result has been achieved**(b)****M1:** Use  $T = \frac{\lambda x}{a}$  to form equation of motion

Need all 3 terms. Condone sign errors

**A1:** Correct unsimplified equation**A1:** cao**(c)****B1:** Seen or implied**M1:** Form work-energy equation. All 4 terms needed  
Condone sign errors**A1:** Correct unsimplified equation A1A1  
One error in the equation A1A0**A1:** cao**(d)****M1:** Form energy equation**A1:** Correct unsimplified equation**A1:** cao



| Question          | Scheme   | Marks      | AOs          |
|-------------------|--|------------|--------------|
| <b>8(a)</b>       |  |            |              |
|                   | Complete overall strategy to find $v$  | M1         | 3.1a         |
|                   | Use of CLM   | M1         | 3.1a         |
|                   | $2m \times 2u - 5m \times u = 5m \times v - 2m \times w$ , ( $-u = 5v - 2w$ )  | A1         | 1.1b         |
|                   | Use of Impact law:   | M1         | 3.1a         |
|                   | $v + w = e(2u + u)$  | A1         | 1.1b         |
|                   | Solve for $v$ :<br>$-u = 5v - 2w$<br>$6eu = 2v + 2w$   |            |              |
|                   | $7v = u(6e - 1)$ ( $v = \frac{u}{7}(6e - 1)$ )   | A1         | 1.1b         |
|                   | Direction of $Q$ reversed: $v > 0$   | M1         | 3.4          |
|                   | $\Rightarrow 1 \geq e > \frac{1}{6}$   | A1         | 1.1b         |
|                   |  | <b>(8)</b> |              |
| <b>(b)</b>        | $e = \frac{1}{3} \Rightarrow v = \frac{u}{7}, w = \frac{6u}{7}$  | B1         | 2.1          |
|                   | Equation for KE lost   | M1         | 2.1          |
|                   | $\frac{1}{2} \times 2m \left( 4u^2 - \frac{36u^2}{49} \right) + \frac{1}{2} \times 5m \left( u^2 - \frac{u^2}{49} \right)$ | A1<br>A1   | 1.1b<br>1.1b |
|                   | $\frac{1}{2} mu^2 \left( 8 - \frac{72}{49} + 5 - \frac{5}{49} \right) = \frac{40mu^2}{7}$ *                                | A1*        | 2.2a         |
|                   |  | <b>(5)</b> |              |
| <b>(c)</b>        | Increase $e \Rightarrow$ more elastic $\Rightarrow$ less energy lost   | B1         | 2.2a         |
|                   |  | <b>(1)</b> |              |
| <b>(14 marks)</b> |  |            |              |

**Question 8 notes:****(a)****M1:** Complete strategy to form sufficient equations in  $v$  and  $w$  and solve for  $v$ **M1:** Use CLM to form equation in  $v$  and  $w$ 

Needs all 4 terms &amp; dimensionally correct

**A1:** Correct unsimplified equation**M1:** Use NEL as a model to form a second equation in  $v$  and  $w$ . Must be used the right way round**A1:** Correct unsimplified equation**A1:** for  $v$  or  $7v$  correct**M1:** Use the model to form a correct inequality for their  $v$ **A1:** Both limits required**(b)****B1:** Or equivalent statements**M1:** Terms of correct structure combined correctly**A1:** Fully correct unsimplified A1A1

One error on unsimplified expression A1A0

**A1\*:** cso. plus a 'statement' that the required result has been achieved**(c)****B1:** "less energy lost" or equivalent